

MATERIAL SAFETY DATA SHEET

IMPORTANT NOTICE

The information contained in this Data Sheet is to be used in conjunction with the additional information, precautions and instructions for use, which appear on the product label. It is the responsibility of the employer to ensure that all persons who use or handle this product should have access to, and be aware of, the information contained herein. Possession of this Data Sheet does not in itself constitute compliance with HSAW Act or COSHH Regulations.

01 SUBSTANCE IDENTIFICATION

NAME: **Accepta 2707**

USE/APPLICATION: ODOUR BLOCK WITH ODOUR DESTRUCTIVE REAGENTS

SUPPLIED BY: Accepta Ltd
 Statham House
 Talbot Road
 Old Trafford
 Manchester M32 0FP

02 COMPOSITIONAL INFORMATION

PROPRIETARY BLEND OF SURFACTANT & ODOR DETRUCTIVE REAGENTS, NON - HAZARDOUS COMPONENTS

| INGREDIENTS LISTED IN RELEVANT CHIP/EH40 DOCUMENTS | | |
|--|---------------------|----------------------|
| DESCRIPTION | HAZARD IN NEAT FORM | LEVEL IN PRODUCT (%) |
| Polysorbate 80 with 6.5 meo (Cas No 9005-65-6) | LOW ACUTE TOXCITY | 6% |

HAZARD RATING AT TYPICAL NEAT PRODUCT: NONE
 HAZARD RATING AT TYPICAL DILUTED PRODUCT 100-1 NONE

03 HAZARDS IDENTIFICATION

MAIN HAZARD (S): NON-HAZARDOUS PRODUCT

| EXPOSURE ROUTE | SPECIFIC HAZARD (UNDILUTED STATE) |
|----------------|-----------------------------------|
| SKIN | LOW HAZARD VIA THIS ROUTE |
| EYES | MAY CAUSE MILD IRRITATION |
| INGESTION | WILL CAUSE STOMACH UPSET |
| INHALATION | NOT A HAZARD |

04 FIRST AID MEASURES

| EXPOSURE ROUTE | IMMEDIATE TREATMENT/ACTION |
|----------------|---|
| SKIN: | WASH WITH CLEAN WATER |
| EYES: | FLUSH WITH WATER FOR 15 MINS |
| INGESTION: | GIVE MILK OR WATER TO DRINK. SEEK MEDICAL AID |
| INHALATION: | N/A |

| | |
|-----------|-------------------------------|
| 05 | FIRE FIGHTING MEASURES |
|-----------|-------------------------------|

PRODUCTS OF COMBUSTION: OXIDES OF CARBON, HYDROGEN AND NITROGEN
FLAMMABILITY LIMITS: UEL (%) n.d LEL(%) n.d
COMBUSTIBILITY: NON-COMBUSTIBLE AUTO-IGNITION TEMP: n.d °C
EXTINGUISHING AGENTS: ALL EXTINGUISHANTS SUITABLE.
PRECAUTIONS: WEAR SELF-CONTAINED BREATHING APPARATUS

| | |
|-----------|------------------------------------|
| 06 | ACCIDENTAL RELEASE MEASURES |
|-----------|------------------------------------|

PERSONAL: SPILLAGE AREA MAY BE SLIPPERY
OTHER: DO NOT ALLOW SPILLED MATERIAL TO ENTER
STORM DRAINS OR SURFACE WATERWAYS
CLEANUP: ABSORB USING SAND OR EARTH

| | |
|-----------|-----------------------------|
| 07 | HANDLING AND STORAGE |
|-----------|-----------------------------|

HANDLING INSTRUCTIONS: USE PROTECTIVE EQUIPMENT DETAILED IN SECTION 08
STORAGE TEMPERATURE: MINIMUM 0 °C MAXIMUM 25 °C
STORAGE CONDITIONS: IN A COOL DRY PLACE
SUITABLE MATERIALS: PLASTICS UNSUITABLE MATERIALS: MILD STEEL

| | |
|-----------|---|
| 08 | EXPOSURE CONTROL / PERSONAL PROTECTION |
|-----------|---|

| EXPOSURE ROUTE | PREVENTIVE ENGINEERING MEASURES | PERSONAL PROTECTION |
|-------------------------|---------------------------------|---|
| SKIN | | GOOD INDUSTRIAL HYGIENE IS NORMALLY SUFFICIENT |
| EYES | | AVOID EYE CONTACT |
| INGESTION | | DO NOT INGEST |
| INHALATION | | NOT APPLICABLE |
| ADDITIONAL INFORMATION: | | REFER TO SECTION 2 AND HSE GUIDANCE NOTE EH40 TO ESTABLISH CURRENT OEL/MEL VALUES |

| | |
|-----------|---|
| 09 | PHYSICAL AND CHEMICAL PROPERTIES |
|-----------|---|

APPEARANCE: COLOURLESS LIQUID
ODOUR: Odourless
RELATIVE DENSITY: 1.015 (@ 20 ° C)pH (NEAT):8.0pH (10% SOLUTION):7.5
FREEZING POINT: ~0 ° C BOILING POINT: n.d ° C
EVAPORATION RATE: (@ 20 ° C; BUTYL ACETATE=100): n.d
FLASH PT: N/A METHOD: N/A
VAPOUR PRESSURE: n.d at ° C VAPOUR DENSITY (@ 20 ° C; AIR=1)n.d
MISCIBILITY-WATER: MISCIBLE IN ALL PROPORTIONS OTHER: N/A
OTHER PHYSICOCHEMICAL DATA:

| | |
|-----------|---------------------------------|
| 10 | STABILITY AND REACTIVITY |
|-----------|---------------------------------|

GENERAL STABILITY: STABLE
CONDITIONS TO AVOID: EXTREMES OF TEMPERATURE
MATERIALS TO AVOID: DO NOT MIX WITH ANY OTHER PRODUCT
DECOMPOSITION PRODUCTS:

| | |
|-----------|----------------------------------|
| 11 | TOXICOLOGICAL INFORMATION |
|-----------|----------------------------------|

| | |
|--|---|
| ORAL LD ₅₀ : | >10000 mg/kg (SPECIES: ORAL,RAT(CALCULATED)) |
| DERMAL LD ₅₀ : | n.d.mg/kg (SPECIES:) |
| ACUTE (SHORT TERM) EFFECTS: (INCLUDING DELAYED EFFECTS) | NONE KNOWN OR EXPECTED |
| CHRONIC (LONG TERM) EFFECTS; | NONE KNOWN OR EXPECTED |
| EXPOSURE LIMITS: | REFER TO SECTION 2 AND HSE GUIDANCE NOTE EH40 TO ESTABLISH CURRENT OEL/MEL VALUES |
| CARCINOGEN/MUTAGEN | |
| TERATOGEN DATA: | NOT KNOWN |
| OTHER EFFECTS: | NONE KNOWN |

| | |
|-----------|-------------------------------|
| 12 | ECOLOGICAL INFORMATION |
|-----------|-------------------------------|

| | |
|-------------------------|---------------------------------|
| SUMMARY OF EFFECTS: | NOT AN ECOHAZARD |
| BIODEGRADABILITY: | PASSES OECD BIODEGRADATION TEST |
| BIOACCUMULATION DATA | BIOACCUMULATION NOT EXPECTED |
| CHEMICAL OXYGEN DEMAND: | NOT KNOWN |
| AQUATIC TOXICITY: | LOW |

| | |
|-----------|--------------------------------|
| 13 | DISPOSAL CONSIDERATIONS |
|-----------|--------------------------------|

DISPOSAL: ABSORB USING SAND OR EARTH AND DISPOSE AS SOLID WASTE

| | |
|-----------|------------------------------|
| 14 | TRANSPORT INFORMATION |
|-----------|------------------------------|

UN SUBSTANCE ID: IMDG CODE: CLASS: MFAG TABLE No: EmS No: DR/RID CLASS:

| | |
|-----------|-------------------------------|
| 15 | REGULATORY INFORMATION |
|-----------|-------------------------------|

SYMBOLS (1): NONE (2): NONE
WARNINGS:
VOLUNTARY TEXT: KEEP OUT OF REACH OF CHILDREN

| | |
|-----------|--------------------------|
| 16 | OTHER INFORMATION |
|-----------|--------------------------|

The atomisation and spray delivery of any aqueous product is subject to variations in spraying efficiency, wind patterns, product dilution and local land or building features. We strongly recommend that Accepta 2707 installations are regularly checked for floor wetness. Such wet areas, depending on the nature of the floor, may be highly slippery and should be suitably marked as slip-hazard areas. Accepta Ltd strongly recommends the application of a non-slip coating to such floor areas.